

PRODUCT SPECIFICATIONS

SC2-250

STRAIGHT SIDE DOUBLE CRANK



TECHNICAL DATA



MEASUREMENTS

	MEASUREMENTS
Press Tonnage (US Tons/kN)	275/2500
Tonnage Rating (in./mm)	.27/7
Slide Stroke (in./mm)	9.8/250
Press Speed (spm)	20-40
Max. Die Height (in./mm)	21.6/550
Slide Adjustment (in./mm)	4.7/120
Upright Openings T-B (in./mm)	23.6/600
Upright Openings L-R (in./mm)	35.4/900
Slide Area (in./mm)	78.7x27.6/2000x700
Bolster Area (in./mm)	90.6x36.2/2300x920
Main Motor (HP/KW)	40/30
Overall Dimensions (in./mm)	104.3x131.9x192.9/2650x3350x4900
Total Weight (US Tons /Ton)	42/38

- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Eight point long gibs
- Increased tool life, minimum deflection
- High off center load capability
- Parts and services from BCN Technical Services

Contact

Bliss Press USA
1004 East State Street
Hastings, Michigan 49058 | USA
P (800) 64-BLISS (642-5477)
info@blisspressusa.com
www.blisspressusa.com