

PRODUCT SPECIFICATIONS

SC2-400

STRAIGHT SIDE DOUBLE CRANK



- American brand controls
- Fast acting hydraulic overload system
- High rigidity steel welded frame
- Locked eight point long gibs
- Increased tool life, minimum deflection
- Precision machined components
- Parts and services from BCN Technical Services

TECHNICAL DATA

	MEASUREMENTS
Press Tonnage (US Tons/kN)	440/4000
Tonnage Rating (in./mm)	.31/8
Slide Stroke (in./mm)	13.8/350
Press Speed (spm)	20-40
Stroke Down Adjust Up (in./mm)	21.6/550
Slide Adjustment (in./mm)	4.7/120
Upright Openings F-B (inch/mm)	35.4/900
Upright Openings L-R (inch/mm)	124/3150
Slide Area (in./mm)	106.3x55.1/2700x1400
Bolster Area (in./mm)	122.1x55.1/3100x1400
Main Motor (HP/KW)	60/45
Overall Dimensions (in./mm)	165x114x217/4200x2900x5500
Total Weight (US Tons /Ton)	66/60

Contact

Bliss Press USA
1004 East State Street
Hastings, Michigan 49058 | USA
P (888) 554-0325
info@blisspressusa.com
www.blisspressusa.com